

SFKH02+ LCD

Immersion temperature sensor

thermokon[®]
HOME OF SENSOR TECHNOLOGY

Datasheet

Subject to technical alteration
Issue date: 08.06.2017



Application

Immersion sensor with neck pipe in hinged lid enclosure USE complete and integrated thermowell pocket for temperature measurement of gases and liquids in pipework applications.

Types Available

Immersion sensor with display temperature – active 0..10 V

SFKH02+ LCD TRV MultiRange <xx>.08

Immersion sensor with display temperature – active 4..20 mA

SFKH02+ LCD TRA MultiRange <xx>.08

Immersion sensor with display temperature – active 0..10 V + relay

SFKH02+ LCD TRV MultiRange relay <xx>.08

<xx>: mounting length 50/100/150/200/250/450 mm

MultiRange: Measuring ranges adjustable at the transducer

Security Advice – Caution



The installation and assembly of electrical equipment should only be performed by authorized personnel.

The product should only be used for the intended application. Unauthorised modifications are prohibited! The product must not be used in relation with any equipment that in case of a failure may threaten, directly or indirectly, human health or life or result in danger to human beings, animals or assets. Ensure all power is disconnected before installing. Do not connect to live/operating equipment.

Please comply with

- Local laws, health & safety regulations, technical standards and regulations
- Condition of the device at the time of installation, to ensure safe installation
- This data sheet and installation manual

Notes on Disposal



As a component of a large-scale fixed installation, Thermokon products are intended to be used permanently as part of a building or a structure at a pre-defined and dedicated location, hence the Waste Electrical and Electronic Act (WEEE) is not applicable. However, most of the products may contain valuable materials that should be recycled and not disposed of as domestic waste. Please note the relevant regulations for local disposal.

Build-up of Self-Heating by Electrical Dissipative Power

Temperature sensors with electronic components always have a dissipative power, which affects the temperature measurement of the ambient air. The dissipation in active temperature sensors shows a linear increase with rising operating voltage. This dissipative power has to be considered when measuring temperature. In case of a fixed operating voltage ($\pm 0,2$ V) this is normally done by adding or reducing a constant offset value. As Thermokon transducers work with a variable operating voltage, only one operating voltage can be taken into consideration, for reasons of production engineering. Transducers 0..10 V / 4..20 mA have a standard setting at an operating voltage of 24 V =. That means, that at this voltage, the expected measuring error of the output signal will be the least. For other operating voltages, the offset error will be increased by a changing power loss of the sensor electronics. If a re-calibration should become necessary later directly on the sensor, this can be done by means of a trimming potentiometer on the sensor board.

Remark: Occurring draft leads to a better carrying-off of dissipative power at the sensor. Thus temporally limited fluctuations might occur upon temperature measurement.


Technical Data

| | | |
|-----------------------|--------------------|--|
| Measuring values | | temperature |
| Medium | | gases, fluids |
| Output voltage | | 0..10 V or 0..5 V, min load 10k Ω (live-zero configuration via Thermokon USEapp) |
| Output Amp | TRA | 4..20 mA, max load 500 Ω |
| Output switch contact | Relay | 2 floating contacts for 24 V ~ or 24 V = / 3 A |
| Power supply | TRA | 15..35 V = or 19..29 V ~, 15..35 V = |
| Power consumption | | max. 2,5 W (24 V =) max. 4,3 VA (24 V ~) |
| Measuring range temp. | | -20..+80 °C (default setting), optionally configured via Thermokon USEapp |
| Accuracy temperature | | $\pm 1\%$ of measuring range (typ. at 21 °C) |
| Display | | LCD 29x35 mm with RGB backlight |
| Enclosure | | enclosure USE-M, PC, pure white, cover PC, transparent, with removable cable entry |
| Protection | | IP65 according to EN 60529 |
| Cable entry | TRV TRA Relay | M16, for wire max. $\varnothing=8$ mm M20, for wire max. $\varnothing=10$ mm |
| Connection electrical | | removeable plug-in terminal, max. 2,5 mm ² |
| Neck pipe | | stainless steel V2A, $\varnothing=12$ mm, L=70 mm |
| Pocket | | stainless steel V4A, $\varnothing=8$ mm, thread G 1/2", mounting length: 50 100 150 200 250 450 mm |
| Ambient condition | enclosure | -50..+160 °C (only end of sensor) -35..+70 °C, max. 85% rH short term condensation |


Connection Plan

To change the output voltage range (default 0..10 V to 0..5 V) via jumper, the display must be removed from the board first.


SFKH02+ LCD TRV MultiRange




SFKH02+ LCD TRA MultiRange



SFKH02+ LCD TRV MultiRange Relay



Configuration



The Thermokon bluetooth dongle with micro-USB is required for communication between USEapp and USE-M / USE L (Item No.: 668262). Commercial bluetooth dongles are not compatible.


Application-specific reconfiguration of the devices can be carried out using the Thermokon USEapp. The configuration is carried out in the voltage-supplied state.



The configuration-app and the app description can be found in the download area of our webpage.

→ [Download \(APK-file for Android\)](#)

Dimensions (mm)



L=optional mounting length (see technical data)

Accessories (included in delivery)

Mounting kit 2 (only version TRV & TRA)

• Cable entry M16 • Cover screw • 2 Screws (rounded head)

Item No. 640503

Mounting kit 3 (only version Relay)

• Cable entry M20 • seal insert for double cable entry 2x 6 mm • Cover screw • 2 Screws (rounded head)

Item No. 674133

Accessories (optional)

Bluetooth dongle

Item No. 668262

Cable entry M25 USE white, sealing insert 4x $\varnothing=7$ mm (4 pcs)

Item No. 641364

Bonded pocket St52-3 type ESH110

Item No. 103459

Bonded pocket St52-3 type ESH160

Item No. 103466

Bonded pocket St52-3 type ESH210

Item No. 103473

Bonded pocket St52-3 type ESH260

Item No. 173247

M16 Sealing inserts cable entry (packaging unit 10 pcs.)

| for wire with \varnothing | 3 mm | 5 mm | 7 mm | 8 mm |
|-----------------------------|--------|--------|--------|--------|
| Item No | 641036 | 641012 | 639248 | 641340 |

M20 Sealing inserts cable entry (packaging unit 10 pcs.)

| for wire with \varnothing | 2x6 mm | 2x7 mm | 6 mm | 8 mm |
|-----------------------------|--------|--------|--------|--------|
| Item No | 641319 | 641333 | 641074 | 641081 |